



Mecline >> Attacchi rapidi >> Raccordo girevole >> ARF 3P CORTO



### ARF 3P CORTO

Corto= 1 OR Viton® + AA  
Innesto Ø 14 mm



<b>PRESSIONE NOMINALE</b>	<b>250 bar</b>	<b>25 MPa</b>	<b>3600 psi</b>
<b>PRESSIONE AMMISSIBILE</b>	<b>280 bar</b>	<b>28 MPa</b>	<b>4060 psi</b>
<b>PORTATA NOMINALE</b>		<b>40 l/min</b>	<b>10,6 USGpm</b>
<b>TEMPERATURA NOMINALE</b>		<b>150 °C</b>	<b>302 °F</b>

### Caratteristiche

P/N	ENTRATA	ATTACCO	Tipo	MANOPOLA	PESO		Pz
					g	oz	
4100400001	G 1/2 F	M22x1,5 F	Corto	Corta	122	4,3	25
4100400000	G 1/2 M	M22x1,5 F	Corto	Corto	127	4,5	25
300305	G 3/8 F	M22x1,5 F	Corto	Corta	107	3,8	25
300303	G 1/4 F	M22x1,5 F	Corto	Corta	117	4,1	25
300304	G 3/8 M	M22x1,5 F	Corto	Corta	116	4,1	25
300302	G 1/4 M	M22x1,5 F	Corto	Corta	105	3,7	25